

# Spirent mX3 HSE Modules

## Quint-Speed 4-Port High Speed Ethernet Test Modules

The Spirent mX3 family of multi-speed High Speed Ethernet (HSE) test modules are the industry's first capable of quint-speed operation. Spirent was the first test vendor to introduce 5 speeds on a single test module.

Spirent mX3 high speed Ethernet modules:


- offer the highest protocol emulation performance in the industry
- offer the highest stateful protocol performance
- offer the most feature-rich stateless traffic
- are ideal for testing core/edge service provider routers, application gateways and firewalls

The Spirent mX3 Ethernet multi-speed test modules combine Spirent's industry-leading Layer 2-7 traffic generation and analysis with powerful network emulation and application layer protocols for emulating a wide range of device types, users and protocols. These modules deliver the highest performance for Layer 2-7 testing. Reduced power consumption and quint-speed support results in lower CAPEX and OPEX. These modules are ideal for performance testing of data center and service provider network infrastructure where extreme protocol performance is required. They are targeted for testing multi-terabit routers and high-scale cloud infrastructure, ensuring dataplane QoS with high performance traffic and verifying the scalability of routing, access, application and security protocols.

These modules are designed with four QSFP28 ports that utilize four 25G electrical lanes each to support the latest QSFP form factor transceivers and interconnects. The multi-speed QSFP28 interfaces are combined with Spirent's flexible FPGA logic to allow mode-switching of the mX3 packet generation and analysis engine to operate at 100, 50, 40, 25 and 10 gig speeds. The mX3 module supports hardware options to allow customization for speeds and features.

### Applications

- **Service Provider Core and Edge Routers**—Verify scale, reliability, and performance of Layer 2 & 3 services including IP data and video delivered via unicast routing, multicast routing, switching and MPLS VPN technologies.
- **High Scale Terabit Routers**—Test 100G Ethernet core routers with high scale, multi-protocol topologies.
- **High Capacity Multiservice Routers**—Validate IP throughput with millions of subscribers and per-port line-rate data with minimum-sized packets.
- **Data Center Top of Rack, Spine and Core Switches**—Benchmark capacity of high-density and capacity fabrics using IETF RFC 2544, RFC 2889 and RFC 3918 methodologies with easy test setup using dynamically bound traffic and automated wizards.
- **Carrier Ethernet**—Verify scale, reliability, performance of Ethernet services delivered via Ethernet OAM, MPLS-TP, VPLS, PWE3 Psuedowires, bridged Ethernet, packet transport protocols or combinations of these technologies.



## Features & Benefits

- Hardware options available to allow customers to customize module testing needs for speeds and features
- Enable and disable Clause 74 BASE-R FEC, Clause 91 RS-FEC, and Clause 108 RS-FEC
- Auto negotiation and link training
- QSFP28 connector form-factor supports the latest optical transceivers and copper interconnects
- Low total cost of ownership compared to other test modules in its class:
  - Excellent price-performance ratio that delivers faster time-to-market by combining leading-edge technical innovation with Spirent’s extensive testing experience
  - Intelligent power control to shut down unused test modules and allows faster boot time to bring capacity back on-line quickly
  - More total throughput than the competition for a given power footprint
  - Enhanced chassis software license value—Two to four times the device or end-user emulation per chassis with no increase in software costs
  - Topology emulation lowers Capex by eliminating the need for multiple DUTs in multiprotocol tests
  - Intelligent results gets answers in a fraction of the test time required by competitive products
  - Faster boot and firmware upgrade times mean less downtime in continuous running 24x7 regression test beds
- Spirent TestCenter’s industry-leading Layer 2-3 feature set:
  - “Hardened” system proven for testing from a single port up to 2,100 ports
  - Stress ASIC and backplane designs with live traffic changes. The number of emulated devices, the traffic they emanate and the rate at which they send it can all be changed “on the fly” making for more realistic tests and faster troubleshooting
  - Best-in-industry for measuring ultra-low sub-microsecond latencies with 2.5ns precision and resolution. Latency accuracy up to 10 times better than the competition.
  - 19 different scheduling algorithms available for finding the right traffic to emulate the real world or tax the device’s ability to handle any traffic pattern—from micro-bursts to carefully timed sequences of “killer” frames
- mX3 modules support Spirent TestCenter’s deep analysis system
  - Port counts, rates, errors and protocol summaries provide a high-level view for quick drilldown to specific issues
  - Broadest set of per stream metrics with simultaneous control and data plane results allows most tests to be run in a single pass
  - Real-time traffic filters allow analysis down to specific fields. Multiple metrics can be simultaneously collected and instantly analyzed
  - Dynamic views feature multi-metric extraction, sorting and operation in real-time or post-test
  - Full packet capture enables timing, sequencing and content analysis for individual packets
  - Powerful filters ensure the capture buffer is filled with relevant data
- High performance protocol testing
  - Each module features two, multi-core, Intel Xeon Class CPUs for the highest levels of stateful router and host traffic emulation

## Technical Specifications

Spirent mX3 module				
Maximum Support	Speed	Maximum ports per slot	Maximum ports per STP-N11U chassis	Maximum ports per SPT-N4U chassis
MX3-QSFP28-4-100A	100G Only	4	48	8
MX3-QSFP28-4-125A	100/25G	4/16	48/192	8/32
MX3-QSFP28-4-175A	100/50/25G	4/8/16	48/96/192	8/16/32
MX3-QSFP28-4-150A	100/40/10G	4/4/16	48/48/192	8/8/32
MX3-QSFP28-4-225A	100/50/40/25/10G	4/8/4/16/16	48/96/48/192/192	8/16/8/32/32

**Technical Specifications (cont'd)**

Port density	4-port QSFP28 module options
Media support and FEC options See accessory table below for part numbers	<p>Support varies by module speed mode</p> <ul style="list-style-type: none"> <li>• 100G: 100GBASE-SR4, 100GBASE-CR4, 100GBASE-LR4, plus additional MSA PMDs</li> <li>• 50G: 25/50G Consortium 50GBASE-CR2,</li> <li>• 40G: 40GBASE-SR4, 40GBASE-CR4, 40GBASE-LR4</li> <li>• 25G: 802.3by 25GBASE-CR, 25GBASE-CRS, 25GBASE-SR</li> <li>• 10G: 10GBASE-SR, 10G Copper DAC</li> <li>• QSFP28 to SFP28 breakout cable options</li> <li>• Auto-Negotiation and Link Training for 100G, 50G, 40G and 25G</li> <li>• Clause 74 BASE-R FEC, Clause 91 RS-FEC, and Clause 108 RS-FEC</li> <li>• 25/50G Consortium 50GBase-R FEC CL74, 25/50G Consortium 50GBase RS-FEC CL91</li> <li>• IEEE 25GBASE CR CL74, CL108, CR-S CL74, SR FEC CL108</li> <li>• 25/50G Consortium 25GBase-R FEC CL74, 25/50G Consortium 25GBase RS-FEC CL91</li> </ul>
Line clocking and packet time stamping (modules get their transmit line clocking and time-stamping from the control modules on the SPT-N11U and SPT-N4U)	<ul style="list-style-type: none"> <li>• Stratum-3 rated oscillator is the default time source.</li> <li>• Frame time stamp resolution of 2.5ns.</li> <li>• GPS and CDMA-based external time sources are supported</li> <li>• IEEE 1588v2 and NTP packet-based external time sources are supported</li> <li>• TIA/EIA-95B-based external time sources are supported</li> </ul>
Inter-module and Inter-chassis Time Synchronization	<p>Ports in the same chassis are locked to the internal timing source. For separate systems:</p> <ul style="list-style-type: none"> <li>• Timing chain synchronization with +/- 20ns</li> <li>• Synchronized via GPS or CDMA network</li> <li>• Using NTP or PTP packet-based approaches (requires supporting controller version)</li> </ul>
User reservation	Per-port reservation
Transmit / receive streams per port	64k TX and 128k RX for all speeds
VFDs and Variable Fields	<ul style="list-style-type: none"> <li>• 6 VFDs available for each 1k (100G) and 512 (50/40/25/10G) stream templates</li> <li>• 4m route insertion table entries for all speeds</li> </ul>
Scheduler Mode Support	<ul style="list-style-type: none"> <li>• Port Based - traffic scheduling handled at the port level</li> <li>• Rate Based - key parameters determined at the port level with division among the individual stream blocks</li> <li>• Priority Based - scheduling determined at the stream block level using user-assigned priorities. Precise scheduling of CBR and bursty traffic for QoS testing</li> <li>• Manual Mode - manual control of stream sequence</li> </ul>
Frame length range and controls	100% line rate for frames of 58-16383 bytes controlled by fixed, increment, decrement, random and IMIX modes
Statistics	<ul style="list-style-type: none"> <li>• Nearly 50 transmit stats per port reported in real time. Includes L1-4 counters and rates and checksum and CRC errors</li> <li>• Over 40 real-time measurements per stream including advanced sequencing, latency, jitter and data integrity</li> </ul>
Capture	<ul style="list-style-type: none"> <li>• 1MB per 100G or 40G port</li> <li>• 512kB per 50G port</li> <li>• 256kB per 25G port</li> <li>• Capture software includes sophisticated trigger and filtering controls</li> </ul>
Histograms	Port-level histogram modes for latency, jitter, interarrival time, frame length, sequence run length and sequence difference check
Operating temperature	15 C - 35 C, 20% - 80% RH (non-condensing)

**Spirent TestCenter Protocol Emulation (cont'd)**

Spirent TestCenter protocols available as separately licensed packages. Below is a sample list of sup-ported protocols. Contact Spirent for a full list of capabilities and packages.

<b>Enterprise and data center switch protocol support</b>	<ul style="list-style-type: none"> <li>• OpenFlow 1.3 / 1.0: OpenFlow switch and controller emulation and switch conformance testing</li> <li>• Routing, multicast and bridging: All major IPv4 and IPv6 unicast and multicast routing protocols, IGMPv1/v2/v3, MLDv1/v2, LACP, STP, RSTP and MSTP</li> <li>• Data center: DCBX, FCoE, FIP, 802.1Qbb</li> <li>• Stateful L4-7: HTTP, SIP and FTP</li> </ul>
<b>Service Provider protocol support</b>	<ul style="list-style-type: none"> <li>• SDN/NFV: PCE and Segment Routing</li> <li>• Routing and MPLS: All major IPv4 and IPv6 unicast and multicast routing protocols, RSVP-TE, LDP, VPLS-LDP, VPLS-BGP, BGP/MPLS-VPN, Fast Reroute, EVPN, mVPN, P2MP-TE, BFD, TWAMP and PWE3 (RFC4447)</li> <li>• Access: ANCP, PPPoE, DHCP, L2TP, IGMPv1/v2/v3, MLDv1/v2, DHCPv6 and PPPoEv6</li> <li>• Carrier Ethernet and bridging: LACP, STP, RSTP and MSTP, 802.1ag CFM, Y.1731, PBB, PBB-TE, Link OAM</li> <li>• Stateful L4-7: HTTP, SIP and FTP, Unicast/Multicast RTSP and RAW TCP</li> <li>• Mobile Backhaul: MPLS-TP, 1588v2 and Synchronous Ethernet</li> </ul>

**Ordering Information**

**Test Modules**

Base Package Description*	Part Number
SPIRENT MX3 100GBE ONLY QSFP28 4-PORTS	MX3-QSFP28-4-100A
SPIRENT MX3 100 25GBE QSFP28 4-PORT	MX3-QSFP28-4-125A
SPIRENT MX3 100 40 10GBE QSFP28 4-PORT	MX3-QSFP28-4-150A
SPIRENT MX3 100 50 25GBE QSFP28 4-PORT	MX3-QSFP28-4-175A
SPIRENT MX3 100 50 40 25 10GBE QSFP28 4-PORT	MX3-QSFP28-4-225A

\*Additional Base Packages can be created on request, based on any desired speed combinations.

**Accessories for QSFP28 interfaces**

Optical transceiver QSFP28 100GBASE-SR4 MMF 850NM	ACC-6095A
Optical Transceiver QSFP28 100GBASE-LR4 SMF 1310NM	ACC-6096A
Copper DAC QSFP28 100GBASE-CR4 1M	ACC-1034A
Copper DAC QSFP28 100GBASE-CR4 3M	ACC-1035A
Copper DAC QSFP28 100GBASE-CR4 5M	ACC-1038A

**Speed Upgrades\*\***

100G HARDWARE SPEED OPTION FOR MX3-QSFP28-4	HWO-MX3-QSFP28-4-100G
50G HARDWARE SPEED OPTION FOR MX3-QSFP28-4	HWO-MX3-QSFP28-4-50G
40G HARDWARE SPEED OPTION FOR MX3-QSFP28-4	HWO-MX3-QSFP28-4-40G
25G HARDWARE SPEED OPTION FOR MX3-QSFP28-4	HWO-MX3-QSFP28-4-25G
10G HARDWARE SPEED OPTION FOR MX3-QSFP28-4	HWO-MX3-QSFP28-4-10G

\*\*For when you buy a Base Package and later decide to add a new speed to it.

**Contact Us**

For more information, call your Spirent sales representative or visit us on the web at [www.spirent.com/ContactSpirent](http://www.spirent.com/ContactSpirent).

[www.spirent.com](http://www.spirent.com)

© 2018 Spirent Communications, Inc. All of the company names and/or brand names and/or product names and/or logos referred to in this document, in particular the name "Spirent" and its logo device, are either registered trademarks or trademarks pending registration in accordance with relevant national laws. All rights reserved. Specifications subject to change without notice.

Americas 1-800-SPIRENT  
+1-800-774-7368 | [sales@spirent.com](mailto:sales@spirent.com)

US Government & Defense  
[info@spirentfederal.com](mailto:info@spirentfederal.com) | [spirentfederal.com](http://spirentfederal.com)

Europe and the Middle East  
+44 (0) 1293 767979 | [emeainfo@spirent.com](mailto:emeainfo@spirent.com)

Asia and the Pacific  
+86-10-8518-2539 | [salesasia@spirent.com](mailto:salesasia@spirent.com)