

Spirent TestCenter™

EVPN Emulation

An Ethernet VPN (EVPN) enables you to connect a group of dispersed customer sites using a Layer 2 virtual bridge. As with other types of VPNs, an EVPN is comprised of customer edge (CE) devices (host, router, or switch) connected to provider edge (PE) devices. The PE devices can include an MPLS edge switch (MES) that acts at the edge of the MPLS infrastructure.

Features

- EVPN capability negotiation
- EVPN Route Types 1 to 5
- Multi-homing with Aliasing label
- Designated Forwarder Election with split horizon label (3 label)
- VXLAN Overlay
- MAC mobility
- Provider Backbone Bridging (PBB) EVPN
- Traffic Binding for MPLS, VXLAN and MAC-in-MAC
- Ease of use wizards to aid in complex topology configuration

Benefits

- Quickly assess the performance and scalability of your EVPN solution
- Use wizard to easily build, configure, setup complex topologies
- Comprehensive support for most data encapsulations MPLS, VXLAN and MAC-in-MAC

Spirent’s EVPN RFC 7432 emulation package allows easy configuration and management of complex EVPN topologies. With Spirent’s complete protocol and traffic EVPN wizard, you will be able to emulate vast number of VTEPs, PEs, and CE devices and validate their performance and scalability under various scenarios including unicast, multicast, single homing, and multihoming.




Figure 1: EVPN topology diagram

EVPN emulation is well integrated with Spirent’s full protocol support - BGP, MPLS, and VXLAN. EVPN is supported on all Ethernet interfaces from 1Gig to 100Gig (with LAG), and Virtual and includes full automation support with “Save AS Script” and the “Command Sequencer”.




Figure 2: EVPN wizard configuration

Spirent Services

Spirent Global Services provides a variety of professional services, support services and education services—all focused on helping customers meet their complex testing and service assurance requirements. For more information, visit the Global Services website at www.spirent.com or contact your Spirent sales representative.

spirent.com

AMERICAS 1-800-SPIRENT
+1-818-676-2683 | sales@spirent.com

EUROPE AND THE MIDDLE EAST
+44 (0) 1293 767979 | emeainfo@spirent.com

ASIA AND THE PACIFIC
+86-10-8518-2539 | salesasia@spirent.com

Technical specifications

- EVPN capability negotiation
- **Type-1:** Ethernet Auto Discovery (AD) route with per ESI route and per EVI route
- **Type-2:** MAC /IP Advertisement route
- **Type-3:** Inclusive Multicast Ethernet Tag route
- **Type-4:** Ethernet Segment route
- **Type-5:** IP Prefix route
- Traffic binding to MPLS MAC labels, VXLAN and MAC-in-MAC encapsulations
- MAC VRF
- Multi-homing with Aliasing Label
- Designated Forwarder Election with ESI or Split Horizon label (3-label)
- All Active / Single Active Aliasing and Load Sharing
- Fast Convergence – with Ethernet segment withdraw/re-advertise
- Flood Label Support – Multicast flooding for BUM(Broadcast, Unknown Unicast, Multicast) traffic
- Default Gateway Extended Community Support
- Router Mac Extended Community Support
- Label 2 – L3 VNI or IP VRF
- MAC mobility (Sticky MAC) with MAC Extended Community
- Encapsulation extended community for VXLAN Overlay
- Ease of use wizards to aide in complex topology configuration

EVPN results

- Connection State
- Open Counters
- Route Advertised and Withdrawn Counters
- Route by type Counters
- All Standard BGP Counters

RFCs and Drafts

- EVPN – RFC 7432
- Network Virtualization Overlay using EVPN for VXLAN – IETF Draft Bess-evpn-overlay-01
- IP Prefix Advertisement in EVPN – IETF Draft Bess-evpn-prefix-advertisement-01
- Router Mac Extended Community & IP VRF (L3 VNI) in Label 2 – IETF Draft Bess-evpn-inter-subnet-forwarding-00
- PBB EVPN – IETF Draft L2VPN-PBB-EVPN-10

Requirements

- Standard Spirent TestCenter with Traffic Generator and Analyzer
- Routing package requirements
 - Unicast Routing BPK-1004A/B
 - MPLS BPK-1006A/B

Supported platforms

- Supported on the Spirent Ethernet modules
- Supported on Spirent TestCenter Virtual
- Supported on Spirent TestCenter C1 and 50

Ordering information

- | | |
|---|-----------|
| ▪ EVPN Emulation | BPK-1311A |
| ▪ VXLAN Emulation | BPK-1310A |
| ▪ VXLAN and EVPN with Overlay Solution | SPK-1205A |
| ▪ EVPN and EVPN PBB Solution | SPK-1206A |
| ▪ Provider Backbone Bridging (PBB) EVPN | BPK-1328A |